

centos6配置bond

zbkc

原始配置文件

```
1. DEVICE="eth0"
2. BOOTPROTO="dhcp"
3. HWADDR="00:0C:29:04:AE:65"
4. IPV6INIT="no"
5. NM_CONTROLLED="no"
6. ONBOOT="yes"
7. TYPE="Ethernet"
```

配置文件2

```
1. DEVICE="eth1"
2. BOOTPROTO="dhcp"
3. HWADDR="00:0C:29:04:AE:6F"
4. IPV6INIT="no"
5. NM_CONTROLLED="no"
6. ONBOOT="yes"
7. TYPE="Ethernet"
```

创建/etc/sysconfig/network-scripts/ifcfg-bond0

```
1. DEVICE="bond0"
2. BOOTPROTO="dhcp"
3. IPV6INIT="no"
4. NM_CONTROLLED="no"
5. ONBOOT="yes"
6. TYPE="bond"
7. BONDING_MASTER=yes
8. BONDING_OPTS="mode=0 miimon=100"
```

```
1.
2. DEVICE="eth0"
```

```
3. MASTER=bond0
4. SLAVE=yes
5. USERCTL=no
6. BOOTPROTO=none
7. ONBOOT=yes
8. HWADDR="00:0C:29:04:AE:65"
9. NM_CONTROLLED="no"
```

```
1. DEVICE="eth1"
2. MASTER=bond0
3. SLAVE=yes
4. USERCTL=no
5. BOOTPROTO=none
6. ONBOOT=yes
7. HWADDR="00:0C:29:04:AE:6F"
8. NM_CONTROLLED="no"
```

换模式重启就可以了

检查bond模式

```
cat /proc/net/bonding/bond0
```